

12 VDC Switching Power Supplies**Product Features**

- **Solid State Electronically-Regulated**
- **Fold-Back Current Limiting**
 - ▶ Protects power supply from excessive current & continuous shorted output
- **Crowbar Over-Voltage Protection**
 - ▶ On all models (except RS-3A, RS-5A, RS-4L, RS-5L)
- **Maintain Regulation & Low Ripple**
 - ▶ At low line input voltage
- **Heavy-Duty Heat Sink**
 - ▶ Chassis mount fuse
- **Three Conductor Power Cords**
 - ▶ On all models (except RS-3A)
- **One Year Warranty**
- **Made in USA**

Product Specifications

Input Voltage	105 - 125 VAC
Output Voltage	13.8 VDC \pm 0.05 Volts (Internally Adjustable: 11-15 VDC)
Ripple	<5mv Peak to Peak (Full load & Low line)

Model Selection Guide

Desktop Model	Continuous Duty (Amps)	ICS (Amps)	Dimensions	Weight (lbs)
SS-10	7	10	1H x 6W x 9D	3.2
SS-12	10	12	1H x 6W x 9D	3.4
SS-18	15	18	1H x 6W x 9D	3.6
SS-25	20	25	3H x 7W x 9D	4.2
SS-30	25	30	3 $\frac{3}{4}$ H x 7W x 9 $\frac{1}{2}$ D	5.0

**Model Selection Guide**

Desktop Model	Continuous Duty (Amps)	ICS (Amps)	Dimensions	Weight (lbs)
SS-25M	20	25	3H x 7W x 9D	4.2
SS-30M	25	30	3 $\frac{3}{4}$ H x 7W x 9 $\frac{1}{2}$ D	5.0



Model Selection Guide

Desktop Model	Continuous Duty (Amps)	ICS (Amps)	Dimensions	Weight (lbs)
SRM-10	7	10	3½H x 19W x 9½D	4.3
SRM-12	10	12	3½H x 19W x 9½D	4.7
SRM-18	15	18	3½H x 19W x 9½D	5.0
SRM-25	20	25	3½H x 19W x 9½D	6.5
SRM-30	25	30	3½H x 19W x 9½D	7.0
SRM-25M	20	25	3½H x 19W x 9½D	6.5
SRM-30M	25	30	3½H x 19W x 9½D	7.0



Model Selection Guide

Desktop Model	Continuous Duty (Amps)	ICS (Amps)	Dimensions	Weight (lbs)
SRM-25-2	20	25	3½H x 19W x 9½D	10.5
SRM-30-2	25	30	3½H x 19W x 9½D	11.0
SRM-25M-2	20	25	3½H x 19W x 9½D	10.5
SRM-30M-2	25	30	3½H x 19W x 9½D	11.0

