

## Plug-In Compact Rackmount & Cabinet Protectors

Bring power safely and conveniently to wherever you need it with a full line of standard and custom **Plug-In Rackmount & Cabinet** Units. These units are ideal for use in a wide variety of settings, including relay racks and cabinets, laboratories, workshops, classrooms and offices.















**Plug-In Rackmount & Cabinet** units include compact, 90°, deluxe control, industrial, hospital grade, and international units. Most are available in both 15 and 20 Amp configurations.

### Product Features

- **User-Ready Units**
  - ▶ Plug-in units provide power distribution in a portable, plug-in unit.
- **Rugged Construction**
  - ▶ Durable 2" x 1¾" (44mm x 51mm) or 3½" x 2" (89mm x 44mm) aluminum housing. Some plug-in units are available with an impact-resistant plastic housing.
- **Space Saving**
  - ▶ Rackmount units fit standard 19" (482mm) relay racks. Compact 1U design takes up minimum space. 23" (584mm) units available.
- **Low Profile**
  - ▶ Cabinet units offer a narrow 1½" x 1 3/16" (38mm x 20mm) aluminum housing.
- **Aesthetically Pleasing**
  - ▶ Rackmount units have a black matte finish and a black cord. Cabinet, compact and industrial units have a grey finish and a black cord. Deluxe control and 20 Amp units have a putty white finish and a black cord. Most units with a putty white finish have a putty white cord. Hospital grade units have a white finish and a white cord.
- **Flexible Mounting**
  - ▶ Each unit features one of four different mounting types. Each mounting method has been designed to optimize the performance of the product. Complete mounting hardware and installation instructions are included with every unit.
- **Cord Properly Rated To Load Requirements**
  - ▶ 15 Amp units have a 14/3 SJT cord and a NEMA 5-15P plug. 20 Amp units have a 12/3 SJT cord and a NEMA 5-20P or NEMA 1%-20P plug.
- **Lighted Switch**
  - ▶ Most units have lighted ON/OFF switches to control power to the unit.
- **Resettable Circuit Breaker**
  - ▶ Provides overload protection
- **Product Warranty**
  - ▶ Two-Year
- **UL Recognized or Listed And CSA Certified**
  - ▶ Rackmount units are UL recognized components. All other units are UL listed and meet UL1363 standards. All 15A units are CSA certified.

## Model Selection Guide

### Compact Plug-In Outlets

Model	Description/Specifications	Dimensions
 <b>UL100BC/UL100BD</b>	5 outlets.	6' (1.8m) or 15' (4.6m) cord. Length 9¼" (235mm). Receptacle center-to-center 1¼" (32mm).
 <b>UL101BC/UL101BD</b>	4 outlets.	6' (1.8m) or 15' (4.6m) cord. Length 9¼" (235mm). Receptacle center-to-center 1¼" (32mm).
 <b>UL104BC/UL104BD</b>	4 outlets, lighted switch.	6' (1.8m) or 15' (4.6m) cord. Length 9¼" (235mm). Receptacle center-to-center 1¼" (32mm).
 <b>UL204BC/UL204BD</b>	7 outlets, lighted switch.	6' (1.8m) or 15' (4.6m) cord. Length 13" (330mm). Receptacle center-to-center 1¼" (32mm).
 <b>UL205BC/UL205BD</b>	8 outlets	6' (1.8m) or 15' (4.6m) cord. Length 13" (330mm). Receptacle center-to-center 1¼" (32mm).
 <b>UL206BC/UL206BD</b>	6 outlets	6' (1.8m) or 15' (4.6m) cord. Length 12¼" (311mm). Receptacle center-to-center 1¼" (32mm).
 <b>UL207BC/UL207BD</b>	6 outlets, lighted switch.	6' (1.8m) or 15' (4.6m) cord. Length 12¼" (311mm). Receptacle center-to-center 1¼" (32mm).
 <b>UL218BC/UL218BD</b>	8 outlets, lighted switch.	6' (1.8m) or 15' (4.6m) cord. Length 15" (381mm). Receptacle center-to-center 1¼" (32mm).
 <b>UL210BC/UL210BD</b>	10 outlets, lighted switch. Putty white finish.	6' (1.8m) or 15' (4.6m) cord. Length 13" (330mm). Width 3½" (89mm). Receptacle center-to-center 2" (49mm).
 <b>UL1090BC/UL1090BD</b>	4 outlets, lighted switch. Receptacles rotated 90° and spaced to accommodate transformers.	6' (1.8m) or 15' (4.6m) cord. Length 16" (406mm). Receptacle center-to-center 3" (76mm).
 <b>R610/R612</b>	6 outlets, lighted switch. Putty white finish.	6' (1.8m) or 15' (4.6m) cord. Length 12¼" (311mm). Receptacle center-to-center 1¼" (32mm).
 <b>P6/P6-15</b>	6 outlets, lighted switch. Putty white finish, plastic housing.	6' (1.8m) or 15' (4.6m) cord. Length 12¼" (311mm). Receptacle center-to-center 1¼" (32mm).