

Point-of-Use Perma Power Computer Grade Surge Protectors

The **Point-of-Use Surge Protector Series** keeps your critical systems functioning properly by dissipating and diverting excess voltage.

Electrical surges can penetrate any AC power system via telephone and communication lines, or through any other wires that enter a building. Surges and noise are also generated by fluorescent lighting, office machines, electric motors, and HVAC equipment.

Point-of-Use Surge Protectors provide maximum protection for advanced electronic equipment such as personal computers, fax machines, home electronics and appliances.










Product Features

- **All Lines Are Protected**
 - ▶ Units provide surge and noise protection on all three modes (L-N, L-G, and N-G). Units also have thermal protection on all three lines.
- **330V UL1449 Clamping Level**
 - ▶ Outstanding protection against harmful surges
- **EMI/RFI Noise Reduction**
 - ▶ Protects against data disruption due to electromagnetic or radio frequency interference
- **Rugged Construction**
 - ▶ Durable 2" x 1¾" (44mm x 51mm) aluminum housing. Some units are available with an impact resistant plastic housing.
- **Aesthetically Pleasing**
 - ▶ Putty white finish and putty white cord blend with any decor. Hospital Grade units have a white finish and a white cord.
- **Cord Properly Rated To Load Requirements**
 - ▶ 15A units have a 14/3 SJT cord and a NEMA 5-15P plug. 20A units have a 12/3 SJT cord and a NEMA 5-20P plug.
- **Lighted Switch**
 - ▶ Most units have a lighted ON/OFF switch to control power to the unit
- **Protection Indication**
 - ▶ All units have protection indication light(s) to show the status of the unit
- **Resettable Circuit Breaker**
 - ▶ Provides overload protection
- **Up To Lifetime Product Warranty**
 - ▶ With connected equipment warranty up to \$30,000
- **UL Listed And CSA Certified**
 - ▶ All units are UL listed and meet UL1449 2nd edition standards. 15A units are CSA certified.








Product Specifications

Perma Power Computer Grade Specifications	
Surge Protection Circuitry	Single Stage
UL1449 Clamping Level	330 Volts
Maximum Surge Current	13,000 Amps
Noise Reduction	40 dB
Response Time	Less than 1 nanosecond
Product Warranty	5-Year
Connected Equipment Warranty	\$10,000

Model Selection Guide

Perma Power Computer Grade Surge Protectors		
Model	Description/Specifications	Dimensions
 M5BZ	5 outlets, lighted switch. Receptacles rotated 90° and spaced to accommodate transformers.	6' (1.8m) cord. Length 21" (533mm).
 M6BZ/M6BZ-15	6 outlets, lighted switch.	6' (1.8m) or 15' (4.6m) cord. Length 13¼" (337mm).
 M6BZM/M6BZM-15	6 outlets, lighted switch. Phone/Fax protection.	6' (1.8m) or 15' (4.6m) cord. Length 16" (407mm).
 M6BZR/M6BZR-15	6 outlets, remote switch.	6' (1.8m) or 15' (4.6m) cord. Length 13¼" (337mm).
 M5BZIEC	5 250 VAC IEC outlets, lighted switch. Gray finish 10 Amps single pole circuit breaker. Power cord not included. UL 1950 Information Technology Listed. Not listed to UL1449.	Length 18" (457mm).
 M620BZLS/M620BZLS-15	6 20 Amp outlets, lighted switch.	6' (1.8m) or 15' (4.6m) cord. Length 18" (457mm).
 RT610/RT612	6 outlets, lighted switch. Fail-safe auto shutdown cuts power to equipment if surge element fails.	6' (1.8m) or 15' (4.6m) cord. Length 13¼" (337mm).

Perma Power Computer Grade Surge Protectors (...continued)

Model	Description/Specifications	Dimensions
 <p>SR10</p>	<p>6 outlets, lighted switch. Plastic housing.</p>	<p>6' (1.8m) cord. 13¼" x 2½" x 1½" (337mm x 64mm x 40mm).</p>
 <p>SRD10</p>	<p>6 outlets, lighted switch. Plastic housing. Phone/Fax protection.</p>	<p>6' (1.8m) cord. 13¼" x 2½" x 1½" (337mm x 64mm x 40mm).</p>
 <p>PR610</p>	<p>6 outlets, lighted switch. Plastic housing. Maximum surge current 6500 Amps.</p>	<p>6' (1.8m) cord. 11¾" x 2¼" x 1½" (298mm x 57mm x 38mm).</p>
 <p>PXD309</p>	<p>3 outlet wall plug. Phone/Fax protection. Plastic Housing.</p>	<p>4½" x 1" x 3¾" (114mm x 25mm x 95mm).</p>
 <p>PXD329</p>	<p>3 outlet wall plug. Dual Phone/Fax protection. Plastic Housing.</p>	<p>4½" x 1" x 3¾" (114mm x 25mm x 95mm).</p>
 <p>PXDC309</p>	<p>3 outlet wall plug. Phone/Fax and coax protection. Plastic Housing.</p>	<p>4½" x 1" x 3¾" (114mm x 25mm x 95mm).</p>
 <p>PR609</p>	<p>6 outlet wall plug. Maximum surge current 6500 Amps. Plastic Housing.</p>	<p>5" x 3 3/8" x 1¾" (127mm x 86mm x 44mm).</p>