

Ultra-compact, high performance charger for worldwide charging

Available in:

10 A
12 V



TRUECHARGE2 Battery Chargers lead the industry with a small footprint and ultra-compact design. Designed for marine and commercial applications worldwide, the TRUECHARGE2 10-amp replaces the former best-selling, first-generation TRUECHARGE 10TB unit and features universal auto ranging input voltage (90 Vac to 265 Vac, 47 to 63 Hz), which can be used in most parts of the world. The TRUECHARGE2 10-amp is smaller and lighter than its predecessor and can be mounted in a variety of positions.

The TRUECHARGE2 10-amp charger uses power factor correction to deliver a full three-stage charge cycle. As a result, the charger requires less incoming AC power to operate at its peak efficiency, freeing up more usable AC power for onboard electronics.

Performance Features

- » Microprocessor-controlled, multistage charging algorithms
- » Charges flooded, gel, AGM or lead-calcium batteries
- » Power factor corrected, temperature-compensated charging
- » Mounting is possible in a variety of orientations and in areas where space is limited
- » Easy access to AC and DC wiring from one side
- » Tested to conform to ingress protection rating IP32 and meets UL1564, UL1236 including marine supplement and ABYC standards

Protection Features

- » Reverse battery polarity protection
- » Drip-proof design
- » Over temperature protection
- » DC over-voltage protection
- » Battery overcharging protection

Three-Stage Charging

Multistage charging ensures batteries receive optimum charging, but with minimal wear and tear, regulating the voltage and current delivered to the batteries in three automatic stages:

- » Bulk: Replaces 70-80% of the battery's state-of-charge at the fastest possible rate
- » Absorption: Replenishes the remaining 20-30% of charge, bringing the battery to a full charge at a slow, safe rate
- » Float: Voltage is reduced and held constant in order to prevent damage and maintain batteries at a full charge

Power Factor Corrected (PFC) Charging

Less shorepower is required for charging batteries, freeing up more usable AC power for running electrical devices and appliances and reducing the likelihood of tripping shorepower breakers.

Applications:



Recreational vehicles



Marine



Heavy duty trucks



Work vehicles



Buses / coaches



Specialty vehicles



ETL listed to CSA Standard C22.2 No. 107.1 and UL 458* with Marine supplement

*For marine supplement compliance drip shield in specific mounting orientation is required. See installation guide



xantrex™
Smart choice for power™

Electrical specifications (@ 25°C unless otherwise noted)		TRUECHARGE2 10
Output current (nominal)		10 A
Output voltage (nominal, depending on settings)		
Charge		14.2 - 15.5 Vdc
Float		13.4 - 13.8 Vdc
Equalize		NA
DC output connections		Two
AC input voltage		90-265 Vac 47-63 Hz 120 Vac, 230 Vac, 240 Vac nominal
Temperature compensation		Three settings
Charger efficiency		> 80%
Battery type		Gel, Flooded, AGM, Pb-Ca
Minimum recommended battery bank size		20 Ah

General specifications	
Operating temperature*	0 to 65°C
Storage temperature	-40 to 80°C
Battery connection	Two positive terminals One negative terminal
Dimensions (H x W x L)	2.7 x 5.4 x 8.8" (70 x 138 x 224 mm)
Weight	3.3 lb (1.5 kg)
Warranty	Two year
Part Numbers	804-1210

Regulatory and environmental compliance

CSA E60335-2-29, UL1564, and UL1236 including the Marine Supplement and drip test. CE Marked for the Low Voltage Directive (safety) and the EMC Directive. Complies with IEC 60335-2-29 including Australian deviations. Ingress protection rating IP32 per EN/IEC 60529. Complies with FCC Part 15B and Industry Canada ICES-003 Class B emissions limits. Complies with ABYC A-31

Note: Specifications are subject to change without notice. *Output may derate above 50°C